



## Esecuzioni / Executions / Bauformen / Exécutions / Ejecuciones

Custodia / Case / Gehäuse	Pla-PB
Boîtier / Bote	Pla-C8
Terminazioni / Terminals / Anschlüsse	CB250
Terminaux / Terminales	CVF150
	FD (Ø ≥ 30mm)
	FS (Ø = 25mm)
G: Cappellotto plastico di protezione Capacitors can be equipped with plastic protective cap (option)	
RS: Resistenza di scarica Capacitors can be equipped with discharge resistor (option)	

## MKA - MK 450 V<sub>ac</sub> series

### Custodia Plastica - Plastic case

Case: Pla-PB + Pla-C8 Terminals: CB250	Case: Pla-PB Terminals: CVF150	Case: Pla-PB + Pla-C8 Terminals: FD + FS	Codolo Snap-in	Snap-in Stud
<p><b>Pla-PB</b> Custodia plastica autoestinguente (V2) con base piana Plane base self-extinguishing (V2) plastic case Selbstverlöschender Kunststoffbecher (V2) mit flachem Boden Boîtier plastique auto-extinguible (V2) sans fixation Bote de plástico autoextinguible (V2) sin fijación</p> <p><b>Pla-C8</b> Custodia plastica autoestinguente (V2) con codolo alluminio M8 Bottom M8 metal stud self-extinguishing (V2) plastic case Selbstverlöschender Kunststoffbecher (V2) mit Bodenbolzen M8 Boîtier plastique auto-extinguible (V2) avec vis métallique de M8 Bote de plástico autoextinguible (V2) con tornillo metálico de M8</p>	<p><b>FD</b> Faston doppio 6,3 x 0,8 mm Double tag 6.3mm x 0.8mm Doppelfachstecker 6.3mm x 0.8mm Cosse double 6.3mm x 0.8mm Faston doble 6.3mm x 0.8mm</p> <p><b>FS</b> Faston singolo 6,3 x 0,8 mm Single tag 6.3mm x 0.8mm Einzelfachstecker 6.3mm x 0.8mm Cosse simple 6.3mm x 0.8mm Faston simple 6.3mm x 0.8mm</p>	<p><b>CVF150</b> (0,5mm ≤50µF) (0,8 mm &gt; 50 µF) Cavetti flessibili di lunghezza 150mm (altre lunghezze a richiesta) Two flexible leads length 150mm (other length or request) Zwei flexible Litzen PVC isoliert 150mm (Verschiedene Kabellänge auf anfrage) Fils PVC souples longueur 150mm (autre longueur sur demande) Hilos PVC flexibles longitud 150mm (otra longitud bajo demanda)</p> <p><b>CB250</b> (0,5mm ≤50µF) (0,8 mm &gt; 50 µF) Cavetti Bipolare di lunghezza 250mm (altre lunghezze a richiesta) Bipolar cable length 250mm (other length or request) Zweiadriges Kabel 250mm (Verschiedene Kabellänge auf anfrage) Câble bipolaire longueur 250mm (autre longueur sur demande) Cable manguera longitud 250mm (otra longitud bajo demanda)</p>		

## MKM 250 - 450 V<sub>ac</sub> series

### Custodia di Alluminio - Aluminium case

Custodia: Alu-PB Terminali: FD - FS	Custodia: Alu-C8 Terminali: FD + FS	AS Dispositivo di sicurezza a sovrappressione / Safety device Sicherheitseinrichtung / Dispositif anti-éclatement Sistema antiexplosivo	Guaina Plastica Protettiva - Protective Plastic Cap
<p><b>Alu-PB</b> Custodia alluminio con base piana Plane base self-extinguishing aluminium case Aluminiumbecher mit flachem Boden Boîtier aluminium auto-extinguible sans fixation Bote de aluminio autoextinguible sin fijación</p> <p><b>Alu-C8</b> Custodia alluminio con codolo Bottom stud self-extinguishing aluminium case Aluminiumbecher mit Bodenbolzen Boîtier aluminium auto-extinguible avec vis métallique Bote de aluminio autoextinguible con tornillo metálico</p>	<p><b>F2.86</b> Faston singolo 2,86 x 0,8 mm Single tag 2.86mm x 0.8mm Einzelfachstecker 2.86mm x 0.8mm Cosse simple 2.86mm x 0.8mm Faston simple 2.86mm x 0.8mm</p> <p><b>FD</b> Faston doppio 6,3 x 0,8 mm Double tag 6.3mm x 0.8mm Doppelfachstecker 6.3mm x 0.8mm Cosse double 6.3mm x 0.8mm Faston doble 6.3mm x 0.8mm</p>	<p><b>FS</b> Faston singolo 6,3 x 0,8 mm Single tag 6.3mm x 0.8mm Einzelfachstecker 6.3mm x 0.8mm Cosse simple 6.3mm x 0.8mm Faston simple 6.3mm x 0.8mm</p> <p><b>RS</b> - (1M Ω ≤ 20 µF) Resistenza di scarica Discharge resistor Entladewiderstand Résistance de décharge Resistencia de descarga</p>	<p><b>AS</b> Dispositivo di sicurezza a sovrappressione Safety device Sicherheitseinrichtung Dispositif anti-éclatement Sistema antiexplosivo</p>