

Pin assignment

Pin assignment number: 2014

Index:

16.10.2013

Connector name: 8-pol.BINDER

Pin-count: 8

Page: 1/1

Pin	Designation	Description	Level	Driver	NC	Colour
1	not connected					
2	Analog-	Analog output	0V			White
3	Startpoint IN	Initial point				Gray
4	Endpoint IN	Final point				Green
5	Analog+	Analog output	0..10V			Black
6	Ground IN	Ground	0V			Blue
7	Supply Voltage IN	Supply voltage	24V +/-10%			Brown
8	not connected					


WARNING !!'

De-energize the system before carrying out wiring work or opening and closing electrical connections !!!

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen !!! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.

德国帝尔(TRelectronic)增压缸位移传感器接线对照表

LA46K 模拟量 系列	 <p>(望向传感器头方向)</p>	插头针脚定义		
		插头针脚	电缆颜色	功能
		针号 1	未连接	
		针号 2	白色	信号地
		针号 3	灰色	Startpoint IN
		针号 4	绿色	Endpoint IN
		针号 5	黑色	信号
		针号 6	蓝色	电源地
		针号 7	棕色	电源 24V
		针号 8	未连接	