



Image shown may not reflect actual package.

STANDBY

**1600 e kW 2000 kVA
50 Hz 1500 rpm 400 Volts**

Caterpillar is leading the power generation marketplace with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.

FEATURES

FUEL/EMISSIONS STRATEGY

- Low fuel consumption

FULL RANGE OF ATTACHMENTS

- Wide range of bolt-on system expansion attachments, factory designed and tested
- Flexible packaging options for easy and cost effective installation

SINGLE-SOURCE SUPPLIER

- Fully prototype tested with certified torsional vibration analysis available

WORLDWIDE PRODUCT SUPPORT

- Caterpillar® dealers provide extensive post sale support including maintenance and repair agreements
- Caterpillar dealers have over 1,600 dealer branch stores operating in 200 countries
- The Cat® S•O•SSM program cost effectively detects internal engine component condition, even the presence of unwanted fluids and combustion by-products

CAT 3516 TA DIESEL ENGINE

- Reliable, rugged, durable design
- Field-proven in thousands of applications worldwide
- Four-stroke-cycle diesel engine combines consistent performance and excellent fuel economy with minimum weight

CAT SR5 GENERATOR

- Matched to the performance and output characteristics of Caterpillar engines
- Industry leading mechanical and electrical design
- Industry leading motor starting capabilities
- High Efficiency

CAT EMCP 3 SERIES CONTROL PANELS

- Simple user friendly interface and navigation
- Scalable system to meet a wide range of customer needs
- Integrated Control System and Communications Gateway

STANDBY 1600 kW 2000 kVA

50 Hz 1500 rpm 400 Volts



FACTORY INSTALLED STANDARD & OPTIONAL EQUIPMENT

System	Standard	Optional
Air Inlet	<ul style="list-style-type: none"> •Single element canister type air cleaner •Service indicator 	<ul style="list-style-type: none"> •Dual element & heavy duty air cleaners (with pre-cleaners) •Air inlet adapters & shutoff
Cooling	<ul style="list-style-type: none"> • Radiator with guard (43°C) • Coolant drain line with valve • Radiator fan and fan drive • Fan and belt guards • Caterpillar® Extended Life Coolant* • Coolant level sensors *Not included with packages without radiators 	<ul style="list-style-type: none"> • Radiator with 50°C ambient capability • Radiator removal • Duct flange • Heat exchanger and expansion tank • Coolant level switch gauge
Exhaust	<ul style="list-style-type: none"> • Dry exhaust manifold • Flanged faced outlets 	<ul style="list-style-type: none"> • Mufflers & Silencers • Stainless steel exhaust flex fittings • Elbows, flanges, expanders & Y adapters
Fuel	<ul style="list-style-type: none"> • Secondary fuel filters • Fuel priming pump • Flexible fuel lines • Fuel cooler* *Not included with packages without radiators 	<ul style="list-style-type: none"> • Water separator • Duplex fuel filter • Primary Fuel Filter
Generator	<ul style="list-style-type: none"> • Class H insulation • Class F temperature (105°C prime/130°C standby) • Winding temperature detectors • Anti-condensation space heaters 	<ul style="list-style-type: none"> • Oversize & premium generators
Power Termination	<ul style="list-style-type: none"> • Bus bar (NEMA and IEC mechanical lug holes)- right side standard • Top and bottom cable entry 	<ul style="list-style-type: none"> • Circuit breakers, UL Listed, 3 pole with shunt trip, 100% rated, choice of trip units, manual or electricity operated (low voltage only) • Circuit breakers, IEC compliant, 3 or 4 pole with shunt trip (low voltage only, choice of trip units, manual or electrically operated) • Shroud cover for bottom cable entry • Power terminations can be located on the left and/or rear as an option. Also, multiple circuit breakers can be ordered (up to 2)
Governor	<ul style="list-style-type: none"> • Woodward 2301 Isochronous governor 	<ul style="list-style-type: none"> • Load share module
Control Panel	<ul style="list-style-type: none"> • EMCP 3.1 Genset Controller 	<ul style="list-style-type: none"> • EMCP 3.3 • Local & remote annunciator modules • Load share module • Customer Interface Module • Customer Communication Module
Lube	<ul style="list-style-type: none"> • Lubricating oil • Gear type lube oil pump • Oil filter, filler and dipstick • Oil drain lines and valve • Fume disposal 	<ul style="list-style-type: none"> • Oil level regulator • Deep sump oil pan • Electric & air prelube pumps • Manual prelube with sump pump • Duplex oil filter
Mounting	<ul style="list-style-type: none"> • Rails-Engine/Generator/Radiator Mounting • 330 mm (13 in) structural steel rails • Spring type anti-vibration mounts (shipped loose) 	<ul style="list-style-type: none"> • Isolator removal
Starting/Charging	<ul style="list-style-type: none"> • 24 volt starting motor(s) • Batteries with rack and cables • Battery disconnect switch 	<ul style="list-style-type: none"> • Battery chargers (10& 20 Amp) • 45 amp charging alternator • Oversize batteries • Ether starting aids • Heavy duty starting motors • Barring device (manual) • Air starting motor with control & silencer

STANDBY 1600 kW 2000 kVA

50 Hz 1500 rpm 400 Volts



SPECIFICATIONS

CAT GENERATOR

Caterpillar Generator
Frame size..... 1625
Excitation..... IE
Pitch..... 0.6667
Number of poles..... 4
Number of bearings..... Single Bearing
Number of Leads..... 006
Insulation..... UL 1446 Recognized Class H with tropicalization and antiabrasion
IP Rating..... IP23
Alignment..... Pilot Shaft
Overspeed capability - % of rated..... 150
Wave Form..... 002.00
Paralleling kit/Droop Transformer..... Standard
Voltage regulator.3 Phase sensing with selectible volts/Hz
Voltage regulation.....Less than +/- 1/2% (steady state)
Less than +/- 1% (no load to full load)
Telephone Influence Factor..... Less than 50
Harmonic distortion..... Less than 5%

CAT DIESEL ENGINE

3516 TA, V-16, 4-stroke-cycle watercooled diesel
Bore - mm..... 170.00 mm (6.69 in)
Stroke - mm..... 190.00 mm (7.48 in)
Displacement - L..... 69.00 L (4210.64 in³)
Compression ratio..... 13.5:1
Aspiration..... TA
Fuel system..... Electronic unit injection
Governor type..... Woodward

CAT EMCP CONTROL PANELS

- EMCP 3.1 (standard)
 - EMCP 3.3 (optional)
 - Generator mounted rear-facing control panel
 - Emergency stop button
 - 24 Volt DC Control
 - Environmental sealed front face
 - Text alarm / event descriptions
 - Shutdowns with indicating lights for:
 - Low oil pressure
 - High coolant temperature
 - Overspeed
 - Emergency stop
 - Failure to start (overcrank)
 - Low coolant level
 - Controls:
 - Speed adjust
 - Auto/start/stop control
 - Engine cool-down timer
 - Engine cycle crank
 - Alarm acknowledge
 - True RMS metering, 3-phase
 - Digital indications for:
 - RPM
 - Operating hours
 - Oil pressure (psi, kPa or bar)
 - Coolant temperature
 - System DC volts
 - Volts (L-L & L-N), frequency (Hz)
 - Amps (per phase and average)
 - Programmable digital (4) inputs and (4) outputs
- MODBUS isolated data link (RS-485 half-duplex) supports serial communication at data rate up to 115.2 kbaud (*)

*** Consult your Caterpillar Dealer for Details**

STANDBY 1600 ekW 2000 kVA

50 Hz 1500 rpm 400 Volts



TECHNICAL DATA

Open Generator Set - - 1500 rpm/50 Hz/400 Volts	DM7961	
Low Fuel Consumption		
Generator Set Package Performance Genset Power rating @ 0.8 pf Genset Power rating with fan	2000 kVA 1600 ekW	
Coolant to aftercooler Coolant to aftercooler temp max	82 ° C	180 ° F
Fuel Consumption 100% load with fan 75% load with fan 50% load with fan	420.9 L/hr 317.4 L/hr 225.9 L/hr	111.2 Gal/hr 83.8 Gal/hr 59.7 Gal/hr
Cooling System¹ Air flow restriction (system) Air flow (max @ rated speed for radiator arrangement) Engine Coolant capacity with radiator/exp. tank Engine coolant capacity Radiator coolant capacity	0.12 kPa 1543 m ³ /min 398.0 L 233.0 L 165.0 L	0.48 in. water 54491 cfm 105.1 gal 61.6 gal 43.6 gal
Inlet Air Combustion air inlet flow rate	125.0 m ³ /min	4414.3 cfm
Exhaust System Exhaust stack gas temperature Exhaust gas flow rate Exhaust flange size (internal diameter) Exhaust system backpressure (maximum allowable)	491.1 ° C 334.6 m ³ /min 203.2 mm 6.7 kPa	916.0 ° F 11816.3 cfm 8.0 in 26.9 in. water
Heat Rejection Heat rejection to coolant (total) Heat rejection to exhaust (total) Heat rejection to aftercooler Heat rejection to atmosphere from engine Heat rejection to atmosphere from generator	1055 kW 1534 kW 237 kW 167 kW 87.8 kW	59998 Btu/min 87238 Btu/min 13478 Btu/min 9497 Btu/min 4993.2 Btu/min
Alternator² Motor starting capability @ 30% voltage dip Frame Temperature Rise	4978 skVA 1625 125 ° C	225 ° F
Lube System Sump refill with filter	401.3 L	106.0 gal
Emissions (Nominal)³ NOx mg/nm ³ CO mg/nm ³ HC mg/nm ³ PM mg/nm ³	6731.4 mg/nm ³ 354.8 mg/nm ³ 103.8 mg/nm ³ 34.1 mg/nm ³	

¹ For ambient and altitude capabilities consult your Caterpillar dealer. Air flow restriction (system) is added to existing restriction from factory.

² UL 2200 Listed packages may have oversized generators with a different temperature rise and motor starting characteristics. Generator temperature rise is based on a 40 degree C ambient per NEMA MG1-32.

³ Emissions data measurement procedures are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. Data shown is based on steady state operating conditions of 77°F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load and thus cannot be used to compare to EPA regulations which use values based on a weighted cycle.

RATING DEFINITIONS AND CONDITIONS

Meets or Exceeds International Specifications: AS1359, CSA, IEC60034, ISO 3046, ISO 8528, NEMA MG 1-33, UL508A, 98/37/EC

Standby - Output available with varying load for the duration of the interruption of the normal source power. Average power output is 70% of the standby power rating. Typical operation is 200 hours per year, with maximum expected usage of 500 hours per year. Standby power in accordance with ISO 8528. Fuel stop power in accordance with ISO 3046. Standby ambients shown indicate ambient temperature at 100% load which results in a coolant top tank temperature just below the shutdown temperature.

Ratings are based on SAE J1349 standard conditions. These ratings also apply at ISO 3046 standard conditions.

Fuel rates are based on fuel oil of 35° API [16° C (60° F)] gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.). Additional ratings may be available for specific customer requirements, contact your Caterpillar representative for details. For information regarding Low Sulfur fuel and Biodiesel capability, please consult your Caterpillar dealer.

STANDBY 1600 kW 2000 kVA

50 Hz 1500 rpm 400 Volts



DIMENSIONS

Package Dimensions		
Length	5908.6 mm	232.62 in
Width	2286.0 mm	90 in
Height	2342.0 mm	92.2 in
Weight	16 125 kg	35,549 lb

NOTE: For reference only - do not use for installation design. Please contact your local dealer for exact weight and dimensions. (General Dimension Drawing #2858792).

Performance No.: DM7961

Feature Code: 516DE4Y

Gen. Arr. Number: 2523844

Source: U.S. Sourced

May 27 2008

12770074

www.CAT-ElectricPower.com

© 2008 Caterpillar
All rights reserved.

Materials and specifications are subject to change without notice.
The International System of Units (SI) is used in this publication.

CAT, CATERPILLAR, SAFETY.CAT.COM their respective logos, "Caterpillar Yellow," and the POWER EDGE trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.