

Bearings with external gear

Drawing No. <i>I</i>	Di [mm]	Di M till D, 4 H [kg] (mm)	S S L, l n B M	U (mm) (mm)	电 H. H. [mm] (mm)
161.50.2500.891.41.1503	1453	2796 2309 130	262 5 2375 60 3 3 30	10 2497 2 503	120 120 10 10
161.50.2660.891.41.1503	1544	2956 2469 130	2785 2535 64 3 3 30	12 2657 2663	120 120 10 10
161.50.2800.891.41.1503	1616	3096 2609 130	292 5 2675 72 3 3 30	12 2797 2803	120 120 10 10
161.50.3000.891.41.1503	1733	3296 2809 130	312 5 2875 76 3 3 30	14 2997 3003	120 120 10 10

Bearings with internal gear

162.502500.891.41.1503	1423	2691	2200	130
162.502660.891.41.1503	1515	2851	2360	130
162.502800.891.41.1503	1588	2691	2500	130
162.50.3000.891.41.1503	1706	3191	2700	130

	?
	1 _E
	i _{nn}
L f, ! i b h I l l i l l I d m z x • m k • m	[kN] [kN]
b [mm] [mm] [mm]	
2740 20 137 *10,0 -2,0 120	208,6 417,2
2900 20 145 *10,0 -2,0 120	208,6 417,2
3040 20 152 *10,0 -2,0 120	208,6 417,2
3240 20 162 *10,0 -2,0 120	208,6 417,2

26252375	60	33	30	10	25032497	120	120	10	10	2220	20	111 -10.0	-120	
27852535	64	33	30	12	26632657	120	120	10	10	2380	20	119 -10.0	-120	
2925	2675	72	33	30	12	2803 2797	120	120	10	10	2520	20	126 -10.0	-120
3125	2875	76	33	30	14	3003 2997	120	120	10	10	2720	20	136 -10.0	-120

208,6 417,2
208,6 417,2
208,6 417,2
208,6 417,2