

请按照选型步骤①~④选择型式和参数后进行订购。



Order
订货范例

型式①Type — ②皮带编号 · ③皮带公称宽度 — ④齿数
TBOA — H100 — 1100

型式			④齿数 下限~上限	皮带宽度 (mm)	容许张力(N)		适用连接金属件	
① Type	② 皮带种类	③ 皮带公称宽度			氯丁橡胶	聚氨酯		
TJ-TBOG (氯丁橡胶) TJ-TBO (聚氨酯)	XL	25	30 ~ 3937	6.4	-	66	TBCK-XL025	
		37		9.5	47	102	TBCK-XL037	
		50		12.7	70	142	TBCK-XL050	
	L	50	30 ~ 2099	12.7	95	259	TBCK-L050	
		75		19.1	165	387	TBCK-L075	
		100		25.4	-	519	TBCK-L100	
	H	75	45 ~ 1574	19.1	-	397	TBCK-H075	
		100		25.4	-	529	TBCK-H100	
		150		38.1	-	799	TBCK-H150	
		200		50.8	-	1093	TBCK-H200	
	TJ-HTBOG (氯丁橡胶) TJ-HTBO (聚氨酯)	S3M	60	40 ~ 6666	6	-	127	TBCK-S3M060
			100		10	-	106	TBCS-S3M100
150			15		-	159	TBCS-S3M150	
S5M		100	50 ~ 4000	10	310	215	TBCK-S5M100	
		150		15	490	323	TBCK-S5M150	
		250		25	-	539	TBCK-S5M250	
S8M		150	60 ~ 2500	15	-	647	TBCK-S8M150	
		250		25	950	1176	TBCK-S8M250	
		300		30	-	1412	TBCK-S8M300	
		400		40	-	1882	TBCK-S8M400	
TJ-PTBOG (氯丁橡胶)		P5M	100	50 ~ 4000	10	287	-	TBCK-S5M100
			150		15	456	-	TBCK-S5M150
	250		25		817	-	TBCK-S5M250	
	P8M	150	60 ~ 2500	15	606	-	TBCK-S8M150	
		250		25	1060	-	TBCK-S8M250	
TJ-TTBO (聚氨酯)	T5	100	40 ~ 4000	10	-	112	TBCK-T5100	
		150		15	-	166	TBCK-T5150	
		200		20	-	225	TBCK-T5200	
		250		25	-	284	TBCK-T5250	
	T10	150	40 ~ 2000	15	-	299	TBCK-T10150	
		200		20	-	397	TBCK-T10200	
		250		25	-	529	TBCK-T10250	
		300		30	-	627	TBCK-T10300	
		400		40	-	862	TBCK-T10400	

		500		50	-	1064	TBCK-T10500
	AT5	100	40 ~ 4000	10	-	147	TBCK-AT5100
		150		15	-	221	TBCK-AT5150
	AT10	150	40 ~ 2000	15	-	469	TBCK-AT10150
		200		20	-	625	TBCK-AT10200
		250		25	-	781	TBCK-AT10250

📍 全长为(齿数×齿距)。

📍 $kgf = N \times 0.101972$