



PIN DESCRIPTION

- 1.VLCD
- 2.VS+
- 3.VS-
- 4.VB0-
- 5.VB1-
- 6.VB1+
- 7.VB0+
- 8.VDD
- 9.VSS
- 10.TST4
- 11.BM0
- 12.CS0
- 13.CD
- 14.WR1
- 15.WR0
- 16.RST
- 17.D0
- 18.D1
- 19.D2
- 20.D3
- 21.D4
- 22.D5
- 23.D6
- 24.D7

6

# HOT DISPLAY

NOTE	DISPLAY TYPE	FSTN/B&W	CONNECTOR	FPC	VIEWING DIRECTION	DRAWN		DATE		MODEL	HTG160160D
	OPERATING VOLTAGE	16.5V	POLARIZER MODE	TRANSFLECTIVE/POSITIVE		CHECKED		DATE		VERSION	A
	DRIVE METHOD	1/160DUTY 1/10BIAS	VIEWING DIRECTION	6 O' CLOCK		APPROVED		DATE		PAGE	1/1
	OPERATING TEMPERATURE	-25°C ~+80°C	STORAGE TEMPERATURE	-30°C ~+80°C		UNIT	mm	UNSPECIFIED TOLERANCE	± 0.2mm		